



STANDARD FEATURES

- Solid rod linkage to the transmission and cutter blade clutch.
- Cuts growth up to 2" (5 cm) thick – Tempered spring steel 26" (66 cm) blade cuts tall weeds, brush, and saplings.
- Hydrostatic transmission provides clutchless speed selection – up to 4.2 mph (6.7 km/h) forward and 1.7 mph (2.7 km/h) reverse.
- 2-year warranty*

*Engines are warranted separately by manufacturer.



Brush Cutter

Product No.	5127-22-01
CE Product No.	5126-22-59
Engine	Honda® GXV390
Displacement (cc)	389
Fuel Capacity, qt (l)	2.2 (2.1)
Starter	Recoil
Max Speed Fwd / Rev, mph (km/h)	4.2 (6.7) / 1.7 (2.7)
Transmission	Hydro-Gear® T2® Transaxle
Transmission Type	Integrated Hydrostatic Pump / Motor
Deck Material	Steel
Cutting Blades / Material Thickness, in (mm)	1 / 0.25 (6.3) Steel
Cutting Width, in (cm)	26 (66)
Cutting Height Min / Max, in (cm)	3 (7.6) / 5 (12.7)
Max Cutting Capacity Diameter, in (cm)	2 (5)
Max Slope Angle	20°
Tires, in (cm)	16 (40.6) Puncture-proof, Bar Tread, Foam-filled
Assembled Dimensions L x W x H, in (cm)	78 x 32 x 41 (198.1 x 81.2 x 104.1)
Dry Weight, lbs (kg)	405 (183.7)

