



18HP



29HP



35HP

STANDARD FEATURES

- Replaceable steel housing liner
- Stack gaskets seal in airflow and lock in debris moisture
- Flexible intake hose
- Flexible discharge hose
- 12V Battery
- 2-year warranty*

*Engines are warranted separately by manufacturer.



49HP



Skid & Tow-Behind TruckLoaders

Skid Mount Swing or Tow Behind	8183-04-01 8184-04-01	8293-04-01 8295-04-01	8353-04-01 8355-04-01	8493-06-01 8495-06-01
CE Product No.	8183-04-59 8184-04-59	N/A	N/A	N/A
Engine	B&S Vanguard™	B&S Vanguard™	B&S Vanguard™	Kohler® Diesel KDI
Engine Power (HP)	18	29	35	49
Fuel Capacity, gal (l) / Fuel Type	1.5 (5.6) / Gasoline	6 (22.7) / Gasoline	7 (26.4) / Gasoline	22 (83.2) / Diesel (FT4)
Emissions Compliance	EVAP / 49-state	EVAP / 49-state	EVAP / 49-state	Final Tier 4 (FT4)
Mount	Skid Mount Swing-Away	Skid Mount Tow Behind	Skid Mount Tow Behind	Skid Mount Tow Behind
Hitch Class Requirements (min)	Class III	Class III	Class III	Class III
Hitch Type	N/A Square Receiver	N/A Ball Coupler	N/A Ball Coupler	N/A Ball Coupler
Starter	Electric / Pull	Electric	Electric	Electric
Impeller Mount / Drive	Taper Lock Hub / Direct	Taper Lock Hub / Direct	Taper Lock Hub / Belt	Taper Lock Hub / PTO clutch
Impeller Diameter, in (cm) / Type	20 (50.8) / Serrated	19.75 (50.2) / Serrated	25 (63.5) / Serrated	25 (63.5) / Serrated
Impeller Blades / # Cutting Points	4 / 48	4 / 48	4 / 48	4 / 48
Impeller Material / Thickness, in (mm)	Steel / 3/8 (9.5)	Steel / 3/8 (9.5)	Steel / 1/2 (12.7)	Steel / 1/2 (12.7)
Air Flow (CFM)	3,510	4,710	6,950	7,600
Housing Liners, in (mm)	3/16 (4.7) Steel	1/4 (6.3) Steel	1/4 (6.3) Steel	1/4 (6.3) Steel
Flexible Intake Hose (D x L)	10" (25.4cm) x 10' (3m)	12" (30.4cm) x 10' (3m)	16" (40.6cm) x 10' (3m)	16" (40.6cm) x 10' (3m)
Flexibe Discharge Hose (D x L)	7" (17.7cm) x 3' (0.9m)	8" (20.3cm) x 5' (1.5m)	12" (30.4cm) x 6' (1.8m)	12" (30.4cm) x 6' (1.8m)
Axle Rating, lbs (kg)	N/A	2,000 (907)	3,500 (1,587)	3,500 (1,587)
Suspension	N/A	N/A	Torflex®	Torflex®
Tire-Wheel	N/A	N/A ST205 / 75 D15	N/A ST205 / 75 D15	N/A ST205 / 75 D15
Assembled Dimensions L x W x H, in (cm)	25 x 29 x 84 (62 x 72 x 213)	40 x 37 x 98 (102 x 94 x 249) 87 x 54 x 109 (221 x 138 x 277)	46 x 51 x 94 (117 x 130 x 239) 99 x 65 x 114 (252 x 165 x 290)	
Dry Weight, lbs (kg)	460 (209) 580 (263)	727 (330) 1,090 (494)	1,155 (524) 1,555 (705)	1872 (849)* 2272 (1031)

*pre-production estimate


ACCESSORIES

MOUNT ACCESSORIES

Item No.	Compatible With:	Description
MP020001.17	8183-04-01	Rotary Arm Mount for 18HP Skid Mount
MP020002.17	8183-04-01	Hitch Mount for 18HP Skid Mount
MP020060.17	8183-04-01	Hitch Mount Swing Arm (included standard on 8184-04-01)



Rotary Arm Mount



Hitch Mount

KITS

Product No.	Tow-Behind Models	Description
MP010012	All Models	Safety Kit (2 Orange Cones w/bracket and Wheel Chocks w/ Storage Box)
MP010032		LED Light Kit (2 LED Lights w/bracket and Wiring Harness)



Hitch Mount Swing Arm